



SAFETY DATA SHEET

according to 1907/2006/EC, Article 31

Page 1/7

Microburst Tranquil Sense

Revision 15 **Revision date** 2013-01-30

SECTION 1: Identification	n of the substance/mixture and of the company/undertaking
1.1. Product identifier	
Product name	Microburst Tranquil Sense
1.2. Relevant identified uses	of the substance or mixture and uses advised against
Product Use	[SU22] Professional uses: Public domain (administration, education, entertainment, services, craftsmen); [PC3] Air care products;
Description	Metered aerosols - Air Neutralizers.
1.3. Details of the supplier o	f the safety data sheet
Company	Rubbermaid Commercial Products LLC
Address	Newell Rubbermaid Europe Sàrl
	Chemin de Blandonnet 10
	CH-1214 Vernier / Geneva / Switzerland
Web	www.rubbermaid.eu/contact
Telephone	+44 (0)8705 686 824
Fax	+44 (0)2030 279 352
Email	sds.CommercialProducts@newellco.com
Local Supplier	
Company	Newell Poland Services Sp. z o. o.
Address	2 UI. Wybickiego
	Manieczki
	Brodnica
	63-112 Paland
14/_L	Poland
Web	www.rubbermaid.eu/contact
Telephone -	+44 (0)8705 686 824
Fax	+44 (0)2030 279 352
1.4. Emergency telephone r	
Emergency telephone	+44 (0)8705 686 824
number	Monday till Friday (08:30 - 17:00)
Intended use	Worlday till Friday (00.30 - 17.00)
interiord doc	Fragranced metered aerosol space sprays designed for use in proprietary automated dispensers
Further information	Tragranced metered aerosor space sprays designed for use in proprietary automated dispensers
	Taskaisal Caminas Danashasat
Informing Department	Technical Services Department.
SECTION 2: Hazards ide	
2.1. Classification of the sub	estance or mixture
2.1.1. Classification -	F+; R12
1999/45/EC	Symbols: F+: Extremely flammable.
Main hazards	Extremely flammable.



Revision 15 Revision date 2013-01-30

2.2. Label elements

The product is classified in accordance with 67/548/EEC.

For professional use only.

F+: Extremely flammable.



Risk phrases

Symbols

Safety phrases

R12 - Extremely flammable.

S2 - Keep out of the reach of children.

S16 - Keep away from sources of ignition - No smoking.

S23 - Do not breathe gas/fumes/vapour/spray.

S51 - Use only in well-ventilated areas.

Precautionary Phrases

P10 - Contains tetramethyl acetyloctahydronaphthalenes. May produce an allergic reaction.

Further information

Classification system

For mixtures, classification is in compliance with Regulation (EC) 1999/45. The classification is in line with current EC lists. It is expanded, however, by information from technical literature and by information furnished by supplier companies.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

67/548/EEC / 1999/45/EC

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification
Isobutane	601-004-00-0	75-28-5	200-857-2		40 - 50%	F+; R12
Propane	601-003-00-5	74-98-6	200-827-9		10 - 20%	F+; R12
Ethanol	603-002-00-5	64-17-5	200-578-6		10 - 20%	F; R11
Isopropanol (Propan-2-ol)	603-117-00-0	67-63-0	200-661-7		1 - 10%	F; R11 Xi; R36 R67
dimethyl phenethyl butyrate		10094-34-5	233-221-8		< 1%	
Linalyl acetate		115-95-7	204-116-4		< 1%	Xi; R38 N; R51/53
Allyl Caproate		123-68-2	204-642-4		< 1%	Xn; R21/22 Xi; R38 N; R51/53
4-Tertiary-butylcyclohexyl acetate		32210-23-4	250-954-9		< 1%	N; R51/53
tetramethyl Acetyloctahydronaphthalenes		54464-57-2	259-174-3		< 1%	Xi; R43 N; R51/53
Ethylene Brassylate		105-95-3	203-347-8		< 1%	N; R51/53

Further information

Regulation (EU) 453/2010 - Substances in compliance with Regulation (EC) 1272/2008.

Isobutane - Flam. Gas 1: H220; GHS02; GHS04;.

Propane - Flam. Gas 1: H220; GHS02; GHS04;.

Ethanol - Flam. Liq. 2: H225; GHS02;.

Isopropanol - Flam. Liq. 2: H225; Eye Irrit. 2: H319; STOT SE 3: H336; GHS07; GHS02;.

Dimethyl phenethyl butyrate - Aquatic Chonic 2: H411; EUH210; GHS07;.

Linalyl acetate - Skin Irrit. 2: H315; Eye Dam. 2: H319; GHS07;.

Allyl caproate - Acute Tox. 3: H301; Acute Tox. 3: H311; Skin Irrit. 2: H315; Eye Irrit. 2: H319;

Aquatic Chronic 2: H411; GHS06; GHS09;.

4-tertiary-Butylcyclohexyl acetate - Aquatic Chronic 2: H411; GHS09;.

Tetramethyl acetyloctahydronaphthalenes - Skin Irrit. 2: H315; Skin Sens. 1: H317; Aquat. Chronic



Revision 15

	Revision date 2013-01-30
Further information	
	2: H411; GHS07; GHS09;.
	Ethylene brassylate - Aquatic Chronic 2: H411; GHS09;.
Additional Information:	Full text for all Risk Phrases mentioned in this section are displayed in Section 16.
Description	Mixture of organic solvents, perfume and propane/iso-butane (propellant).
SECTION 4: First aid measu	
4.1. Description of first aid mea	sures
Inhalation	Move the exposed person to fresh air.
Eye contact	Rinse immediately with plenty of water for 15 minutes holding the eyelids open.
Skin contact	Wash off immediately with plenty of soap and water.
Ingestion	Rinse mouth thoroughly. DO NOT INDUCE VOMITING.
4.2. Most important symptoms a	and effects, both acute and delayed
Inhalation	May cause dizziness and headache.
Eye contact	May cause irritation to eyes.
Skin contact	May cause irritation to skin.
4.3. Indication of any immediate	e medical attention and special treatment needed
Inhalation	If you feel unwell, seek medical advice (show the label where possible).
Eye contact	Seek medical attention.
Skin contact	Seek medical attention if irritation or symptoms persist.
Further information	
	In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).
SECTION 5: Firefighting me	asures
5.1. Extinguishing media	
	Carbon dioxide (CO2). Alcohol resistant foam. Do NOT use water jet.
5.2. Special hazards arising from	m the substance or mixture
	Extremely flammable aerosol. Carbon oxides. Carbon dioxide (CO2).
5.3. Advice for firefighters	
	Wear suitable respiratory equipment when necessary.
Further information	
	Cool fire exposed containers with waterspray.
SECTION 6: Accidental relea	ase measures
6.1. Personal precautions, prote	ective equipment and emergency procedures
	Wear suitable protective equipment. Evacuate personnel to a safe area.
6.2. Environmental precautions	
	No environmental requirements.
6.3. Methods and material for c	ontainment and cleaning up
	Ensure adequate ventilation. Absorb liquid components with liquid binding material (sand, diatomite, acid binders, universal binders, sawdust).
6.4. Reference to other sections	8
	See section 8 + 13 for further information.
SECTION 7: Handling and s	torage
7.1. Precautions for safe handli	



Wear suitable protective equipment.

15 Revision Revision date 2013-01-30

7.2. Conditions for safe storage, including any incompatibilities

Ensure adequate ventilation of the working area.

Keep in a cool, dry, well ventilated area. Heat will increase pressure in sealed containers. Keep away from sources of ignition - No smoking. Pressurised container. Protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use. Do not spray on a naked flame or any incandescent material. Do not store with strong oxidising agents, Strong acids. Protect from heat and direct sunlight. Observe official regulations on storing packagings with pressurised containers.

7.3. Specific end use(s)

Air care products.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1. Exposure Limit Values

Ethanol	WEL 8-hr limit ppm: 1000	WEL 8-hr limit mg/m3 : 1920
	WEL 15 min limit ppm: -	WEL 15 min limit mg/m3: -
Isopropanol (Propan-2-ol)	WEL 8-hr limit ppm: 400	WEL 8-hr limit mg/m3: 999
	WEL 15 min limit ppm: 500	WEL 15 min limit mg/m3: 1250

8.2. Exposure controls

8.2.1. Appropriate
engineering controls

Ensure adequate ventilation of the working area.

8.2.2. Individual protection measures

Adopt best Manual Handling considerations when handling, carrying and dispensing.

Eye / face protection

Avoid contact with eyes.

Skin protection -

Wash hands after handling the product.

Handprotection Respiratory protection

Not normally required.

Further information

Additional Information:

Wash hands during breaks and at the end of the work.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State Colour Aerosol

According to Product specification.

Odour

Characteristic

Vapour pressure

3.5 - 4.5 bar

Relative density

0.619 - 0.645

Explosive

1.8 - 19.0 Vol %

SECTION 10: Stability and reactivity

10.1. Reactivity

Stable under normal conditions.

10.2. Chemical stability

Will not decompose if stored and used as recommended.

10.3. Possibility of hazardous reactions

Strong oxidising agents.

10.4. Conditions to avoid

Store at temperatures above 50 °C. Heat, sparks and open flames.



Revision 15 Revision date 2013-01-30

10.5. Incompatible materials

No data available.

10.6. Hazardous decomposition products

Carbon oxides. Carbon dioxide (CO2).

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Skin corrosion/irritation May cause irritation to skin. May cause allergic reactions in susceptible people.

11.1.4. Toxicological Information

Ethanol	Oral Rat LD50: 6200 - 17800	
	mg/kg	
Isopropanol	Inhalation Rat LC50/4 h: >20 mg/l	Oral Rat LD50: >5000 mg/kg
	Dermal Rabbit LD50: >5000 mg/kg	

SECTION 12: Ecological information

12.1. Toxicity

Ethanol	Algae IC50/72h: 5000 mg/l	Fish LC50/96h: 11400 mg/l	
	No data is available on this product.		
12.2. Persistence and degradability			
	Evaporates readily.		
12.3. Bioaccumulative potential			

Does not bioaccumulate.

12.4. Mobility in soil

Evaporates readily.

12.5. Results of PBT and vPvB assessment

No data is available on this product.

12.6. Other adverse effects

No data available.

Further information

Do not allow product to enter drains.

SECTION 13: Disposal considerations

General information

Dispose of in compliance with all local and national regulations.

Disposal methods

Contact a licensed waste disposal company.

Disposal of packaging

Do NOT reuse empty containers. Empty containers can be sent for disposal or recycling.

SECTION 14: Transport information

Hazard pictograms



14.1. UN number

UN1950



Revision 15 Revision date 2013-01-30

	Revision date 2013-01-30
14.2. UN proper shipping name	
	AEROSOLS
14.3. Transport hazard class(es	; (s)
ADR/RID	2
Subsidiary risk	see SP63
IMDG	2
Subsidiary risk	see SP63
IATA	2
Subsidiary risk	see SP63
14.4. Packing group	
Packing group	-
14.5. Environmental hazards	
Environmental hazards	No
Marine pollutant	No
ADR/RID	
Hazard ID	-
Tunnel Category	(D)
IMDG	
EmS Code	F-D S-U
IATA	
Packing Instruction (Cargo)	203
Maximum quantity	150 kg
Packing Instruction	203
(Passenger)	
Maximum quantity	75 kg
Further information	
Remarks	ADR - Goods are classified as "Limited Quantities" and are therefore excempt from ADR
_	regulations. Check local legislation for domestic transport.
Remarks	IMDG - Goods are classified as "Limited Quantities" and are therefore exempt from IMDG regulations. Check local regulation for domestic transport.
Remarks	"Limited Quantity".
TOTALIO	Enniod addrity.

SECTION 15: Regulatory information

Regulations

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

COMMISSION REGULATION (EU) No 453/2010 of 20 May 2010 amending Regulation (EC) No
1907/2006 of the European Parliament and of the Council on the Registration, Evaluation,
Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency,
amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and
Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and
Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC.

REGULATION (EC) No 1907/2006 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC.

Aerosol product is manufactured in compliance with Commission Directive 2008/47/EC.

15.2. Chemical safety assessment



Revision 15 Revision date 2013-01-30

15.2. Chemical safety assessment	ent
	No data is available on this product.
Further information	
	Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Do not spray on a naked flame or any incandescent material.
SECTION 16: Other informat	tion
Other information	
Revision	This document differs from the previous version in the following areas:. 3 - Further information. 4 - Skin contact. 4 - Skin contact. 9 - 9.1. Information on basic physical and chemical properties (Relative density). 11 - Respiratory or skin sensitisation. 15 - Precautionary Phrases. 16 - General information.
Data sources	Raw Material Data Sheets.
Text of risk phrases in Section 3	Exposure limits. R11 - Highly flammable. R12 - Extremely flammable. R21/22 - Harmful in contact with skin and if swallowed. R36 - Irritating to eyes. R38 - Irritating to skin. R43 - May cause sensitisation by skin contact. R51/53 - Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. R67 - Vapours may cause drowsiness and dizziness.
General information	
	Additional information in compliance with Regulation (EC) 1272/2008. H220 - Extremely flammable gas. H225 - Highly flammable liquid and vapour. H301 - Toxic if swallowed. H311 - Toxic in contact with skin. H315 - Causes skin irritation. H317 - May cause an allergic skin reaction. H319 - Causes serious eye irritation. H336 - May cause drowsiness or dizziness. H411 - Toxic to aquatic life with long lasting effects.
Further information	
	The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process. *.
Informing Department	Technical Services Department.

